

## Canon EOS 700D with EF-S 18-135mm f/3.5-5.6 IS STM Kit



Rating: 5.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 344.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Canon](#)

### Description

- STM Lens Support for Quiet AF in Movies
- 18.0MP APS-C CMOS Sensor
- DIGIC 5 Image Processor
- 3.0 inch (1040k) Vari-Angle Touch Screen LCD
- ISO 100-12800, Expandable to 25600
- Full HD Movie Mode with Movie Servo AF
- 5.0 fps Continuous Shooting
- 9 Point All Cross-Type AF System
- Multi Shot Noise Reduction
- Seven Creative Filters that can be displayed in real time
- Scene Mode Position

### What's in the box

1. Canon EOS 700D DSLR Body (also known as Rebel T5i)
2. Canon EF-S 18-135mm f/3.5-5.6 IS STM
3. Eyecup Ef

- 4. Body cap
- 5. Wide Neck Strap
- 6. Battery Pack LP-E8
- 7. Battery Charger
- 8. USB Interface Cable
- 9. EOS Digital Solution Disc
- 10. Software Instruction Manual CD

| System Cameras (1)         |                   |
|----------------------------|-------------------|
| General                    |                   |
| Camera                     | DSLR              |
| Type:                      |                   |
| Image Sensor               |                   |
| Sensor                     | CMOS              |
| Type:                      |                   |
| Sensor                     | 22.3 x 14.9 mm    |
| Size:                      |                   |
| Effective                  | 18.0 megapixels   |
| Megapixel                  |                   |
| s:                         |                   |
| Viewfinder                 |                   |
| Viewfinde                  | Pentamirror       |
| r Type:                    |                   |
| Coverage:                  | 95 %              |
| Exposure & Shutter Control |                   |
| Min. ISO                   | 100               |
| Sensitivity                |                   |
| :                          |                   |
| Max. ISO                   | 25600             |
| Sensitivity                |                   |
| :                          |                   |
| Min.                       | 30 sec            |
| Shutter                    |                   |
| Speed:                     |                   |
| Max.                       | 1/4000 sec        |
| Shutter                    |                   |
| Speed:                     |                   |
| Continuou                  | 5 fps             |
| s Burst                    |                   |
| Speed:                     |                   |
| Maximum -                  |                   |
| Shots /                    |                   |
| Burst:                     |                   |
| Video Recording            |                   |
| File                       | MOV (Video:       |
| Format:                    | H.264, Sound:     |
|                            | Linear PCM,       |
|                            | recording level   |
|                            | can be manually   |
|                            | adjusted by user) |
| Video Res1920 x 1080       |                   |
| olution:                   | (29.97, 25,       |
|                            | 23.976 fps) 1280  |
|                            | x 720 (59.94, 50  |
|                            | fps) 640 x 480    |
|                            | (30, 25 fps)      |
| HD                         | Yes               |
| Recording                  |                   |
| Display                    |                   |
| LCD Size:                  | 3.0 inch          |
| LCD Reso                   | 1040 k pixels     |
| lution:                    |                   |
| Live View:                 | Yes               |
| Storage                    |                   |
| Memory                     | SD, SDHC or       |

|                          |                                                        |
|--------------------------|--------------------------------------------------------|
| Card                     | SDXC                                                   |
| Type:                    | (UHS-I)card                                            |
| Internal                 | -                                                      |
| Memory:                  |                                                        |
| Power Supply             |                                                        |
| Battery                  | LP-E8                                                  |
| Model:                   |                                                        |
| Battery                  | BG-E8                                                  |
| Grip:                    |                                                        |
| Dimensions               |                                                        |
| Size:                    | 133.1 X 99.8 X<br>78.8 mm                              |
| Weight:                  | 580 g                                                  |
| Camera Features          |                                                        |
| Image Stabilization      |                                                        |
| Sensor                   | Yes                                                    |
| Cleaning:                |                                                        |
| Tilt / Flip              | Yes                                                    |
| Screen :                 |                                                        |
| Full Auto:               | No                                                     |
| Face Detection           |                                                        |
| ection :                 |                                                        |
| HDMI Connection:         | Yes                                                    |
| External Remote Control: | Remote Switch<br>RS-60E3,<br>Remote<br>Controller RC-6 |