Canon XF200 HD Camcorder (PAL)








Rating: 5.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,249.00

Discount:

In Stock!
Ready to Order

Ask a question about this product

Manufacturer: Canon

Description

Product Highlights

- 1920 x 1080, 1/2.84" CMOS Sensor
- 20x Lens with Zoom, Focus, Iris Rings
- 50 Mbps MPEG-2 & 35 Mbps MP4 Recording
- 4:2:2 Color Sampling
- 50i/p and, 25p Frame Rates
- Dual CF and Single SDXC Card Slots
- Dual XLR Inputs, Four Channels of Audio
- Orientable Hand Grip
- HDMI, WiFi, and Ethernet

Image Sensor Size	1/2.84" CMOS Sensor
Video System	PAL
Color Filter System	RGB Primary color filter
Total Pixels	3.09 MP (2208 x 1398)
Effective Pixels	2.91 MP (2136 x 1362)
Zoom Range	20x Optical 1.5x, 3x, 6x Digital
Focal Length	3.67 to 73.4mm
35mm Equivalent Focal Length	28.8 to 576mm (with Dynamic IS)
Aperture Range	f/1.8 to f/16
Minimum Focus Distance	23.6" (60 cm) Across zoom range 10 mm (1 cm) Wide Macro setting
Zoom Speed	Variable speed / Constant speed (16 levels); Fast, Normal, or Slow
Filter Diameter	58 mm
Shutter Speed	1/18 to 1/2000 depending on frame rate
Image Stabilization	Dynamic IS and Powered IS Five-axis image stabilization
White Balance	-50 to +50 White balance offset for RGB
Supported Video Formats / Codecs	AVCHD, MPEG4
Resolutions and Frame Rates	**MXF** (CF card): 50 Mbps: 1920 x 1080 / 50i, 25p; 1280 x 720 / 50p, 25p 35 Mbps: 1920 x 1080 / 50i, 25p; 1440 x 1080 / 50i; 1280 x 720 / 50p, 25p 25 Mbps: 1440 x 1080 / 50i, 25p **MP4** (SD card): 35/24 Mbps: 1920 x 1080 / 50p, 25p 17 Mbps: 1280 x 720 / 50p 9 Mbps: 1280 x 720 / 25p 3 Mbps: 640 x 360 / 25p
Slow and Fast Motion Recording	MXF only:
Maximum Recording Time	128 GB CF Card: Up to 320 mins (1080/50i @ 50 Mbps) 128 GB SD Card: Up to 8 hours (MP4/50p @ 35 Mbps)
Viewfinder	0.45" Color EVF Pixel Count: Approximately 1.5MP
Touchscreen	3.5" (8.77 cm) OLED
Media Card Slots	2 x Compact Flash 1 x SDXC
USB Terminal	USB 2.0 Mini-B, output only
HDMI Output	1 x HDMI
Audio In	2 x XLR female 1 x 3.5 mm Stereo mini jack 2/4-Channel, Linear PCM, 16-Bit, 48 kHz (MXF)
A/V Output	3.5 mm Mini 4-pole Audio/Video Out
Headphone Out	3.5 mm Stereo mini jack
Remote Control Input	2.5 mm Mini jack
Accessory Shoe	Cold shoe
Operating Temperature	Operation: Approx. 23 to 113°F / -5 to 45°C, 60% RH Performance: Approx. 32 to 104°F / 0 to 40°C, 85% RH
Dimensions	6.3 x 7.9 x 13.9" / 16.0 x 20.1 x 35.3 cm (including lens hood with barrier, eyecup, and microphone holder)
Weight	4.2 lb / 1.9 g