

EPSON Stylus Pro 11880 64in printer With UltraChrome K3 Vivid Magenta Ink



Rating: 3.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,997.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Epson](#)

Description
Item: SP11880K3

UPC: 010343867024

Printing Method	9-channel, drop-on-demand Advanced MicroPiezo TFP print head with ink repelling coating technology and Auto Head Alignment and Cleaning technology
Printing Technology	2880 x 1440 dpi
Maximum Resolution	3.5 picoliters with Variable Droplet Technology
Minimum Ink Droplet Size	Epson UltraChrome K3 with Vivid Magenta pigment-based ink
Ink Type	C, LC, VM, VLM, Y, LK, LLK, PK/MK
Ink Palette	Uses 9 individual ink cartridges
Ink Cartridge Configuration	
Performance	
Print Speed	16" x 20" print: 0:50 to 7:39 20"x 30" print: 1:24 to 13:24

Input Buffer	40"x 60" print: 4:08 to 42:10
Printer Duty Cycle	<i>time listed in Min:Sec</i> <i>Not Specified by Manufacturer</i> <i>Not Specified by Manufacturer</i>
Print Archival Life	Cutter life: 2,000 cuts (coated media)
Maximum Paper Width	Up to 200 Years (depending on print media)
Maximum Printable Area	64"
Paper Sizes	63.75" wide with length limited by application, OS, and Driver/RIP used Roll Media with width of 10", 13", 16", 17", 24", 36", 44", 50", 54", 60" & 64"
Borderless Photo Sizes	Cut Sheet from 8.5" x 11" (letter) to 64" wide (any length) Borderless printing with roll media sizes of 10", 13", 16", 17", 24", 36", 44", 50" & 54"
Paper Types	<i>Top and bottom edges can be automatically cut to any length</i>
Maximum Paper Thickness	Inkjet media approved for use with pigment based inks 12.5 mil (roll, tray and top feed slot) 1.5 mm posterboard (rear manual feed slot)
Paper Capacity	Cut Sheets Front feed slots: 1 Sheet
Special Media Support	Roll Media
Connectivity	Limited by total roll diameter of 4" with 2" core or 6" with 3" core)
Computer Interface	Works with non-paper based inkjet media
Compatible Memory Cards	USB 2.0 (Hi-Speed) <i>1.1 compatible</i>
Direct Print Capable	Ethernet (10/100/1000 Base-T) <i>RJ-45 connector</i>
Network Capable	None
PostScript Support	No
	Yes (via Ethernet)
	Optional PANTONE licensed and SWOP certified PostScript Language
	Level 3 Compatible RIP by ColorBurst
	Supported by most leading third-party RIPs and workflows
System & Software Requirements	Windows System <ul style="list-style-type: none"> • Pentium4 3.0 GHz or better processor • Windows XP, XP Pro x64, Vista, Vista x64 • 1GB RAM (2GB recommended) • 30GB free hard drive space • CD-ROM or DVD Drive (4x speed) • USB Port and Shielded USB "AB" Cable (10' max. length) or Ethernet-equipped PC and Cat 6 cable
	Macintosh System <ul style="list-style-type: none"> • PowerPC G5, Intel or higher processor • Macintosh OS X (10.4.9 or higher, 10.5 or higher) • 1GB RAM (2GB recommended) • 30GB free hard drive space • CD-ROM or DVD Drive (4x speed) • USB 2.0 Port and Shielded USB "AB" Cable (10' max. length) or Ethernet-equipped PC and Cat. 6 cable
Physical	
Status Display	2.5" Monochrome Alphanumeric LCD & Indicator LEDs with Printer Activity Lighting System
Image Preview Display	No
Front Panel Controls	Power, Pause/Reset, Left arrow/Paper source, Paper feed up, Paper feed down, Enter/Bar Code, Menu/Clean, Take-up Reel Controls
Power Requirements	110-120 V AC; 50-60 Hz
Dimensions (WxHxD)	92 x 46 x 28" (2337 x 1169 x 712 mm) <i>with stand</i>
Weight	384 lb (175 kg) <i>with stand</i>
Packaging Info	
Package Weight	395.2 lb

