

## HP DesignJet SD Pro MFP- 44in



Rating: 4.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 7,747.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

**Item:** L3S81A

**UPC:** 889296330189

Printer

Applications

Line Drawings

Print Resolution

Margins

Line drawings, renderings, presentations, maps, orthophotos

28 sec/page on A1/D, 103 A1/D prints per hour

Up to 2400 x 1200 optimized dpi

Roll: 0.2 x 0.2 x 0.2 x 0.2" / 5 x 5 x 5 x 5 mm (borderless on photo roll media)

Sheet: 0.2 x 0.67 x 0.2 x 0.2" / 5 x 17 x 5 x 5 mm

Ink Types	Dye-based (C, G, M, pK, Y) Pigment-based (mK)
Ink Cartridges	Cyan, gray, magenta, matte black, photo black, yellow
Line Accuracy	±0.1%
Minimum Line Width	0.0008" / 0.02 mm (HP-GL/2 addressable) Guaranteed: 0.0024" / 0.06 mm (ISO/IEC 13660:2001, E)
Media	Handling: Sheet feed, 2 automatic roll feeds, automatic roll-switching, automatic cutter Roll Size: 11 to 44" / 279 to 111.8 cm Sheet Size: 8.3 x 11" to 44 x 66" / 21 x 27.9 cm to 11.8 x 167.6 cm Standard Sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness: Up to 31.5 mil / 0.8 mm
Memory	32 GB (virtual) 160 GB hard disk
Connectivity	Interfaces: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, EIO Jetdirect accessory slot Print Languages: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI Printing Paths: Printer driver, HP DesignJet ePrint & Share, HP Embedded Web Server, direct printing from USB flash drive, email printing
Acoustic	Sound Pressure: 43 dB (printing), 29 dB (ready) Sound Power: 6.1 B (printing), 4.7 B (ready), 5.6 B (sleep)
Power	Consumption: < 120 W (printing), < 27 W (ready), < 7 W (sleep), 0.1 W (off) Requirements: 100 to 240 VAC ±10%, 50/60 Hz (±3 Hz), 2 A (max)
Certifications & Approvals	Safety: USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic: Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental: ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, FEMP, EPEAT, Bronze
Scanner	
Scanner Type	CIS scan technology
Scan Speed	Color: Up to 6" / 15 cm per second Grayscale: Up to 13" / 33 cm per second
Resolution	Enhanced: 9600 dpi Optical: 1200 dpi
Maximum Scan Width	44" / 111.8 cm
Scan Input Modes	Scan preview, scan to file, scan to email, scan to USB, scan to print, scan to FTP, copy, batch scanning, batch copying, collate copy, copy to simultaneous printers
Media	Handling: Straight-through scan paper path for sheet and cardboard originals Width: Up to 46" / 1168 mm Thickness: Up to 0.08" / 2 mm
Memory	2 GB 500 GB hard disk
Connectivity	Gigabit Ethernet (1000Base-T) Hi-Speed USB 2.0 certified
Acoustic	Sound Pressure: 62 dB (scanning), 30 dB (ready), 30 dB (sleep) Sound power: 6.4 B (scanning), 3.3 B (ready), 3.3 B (sleep)
Power	Consumption: 47 W (scanning), 32 W (ready), 1.8 W (sleep) Requirements: 100 to 240 VAC (±10%), 50/60 Hz, 5 A (max)
Certifications & Approvals	Safety: USA and Canada (UL certified), EU (LVD and EN 60950-1 compliant), Russia (EAC), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KC) Electromagnetic: Compliance for Class A ITE products: EU (EMC Directive), USA (FCC Rules), Canada (ICES), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (MSIP), Russia (EAC) Environmental: ENERGY STAR, WEEE, RoHS (EU, China, Korea, India), REACH, EPEAT, Bronze
General	
Operating Temperature	41 to 104°F / 5 to 40°C
Storage Temperature	-13 to 131°F / -25 to 55°C
Operating Humidity	20 to 80% RH

Dimensions	69.7 x 57.9 x 59.1" / 177 x 147 x 150 cm
Weight	321.9 lb / 146 kg