

HP DesignJet Z3200 PostScript 44in Photo Printer



Rating: 5.0
Price:
Variant price modifier:

Price with discount:
Salesprice with discount:
USD 2,450.00
Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

Item: Q6721BB1K
Part: Q6721B#B1K
UPC: 884420403401

Printing Method	HP Thermal Inkjet
Printing Technology	2400 x 1200 dpi
Maximum Resolution	4.0 pl: Light Cyan, Light Magenta, Light Gray, Photo Black, Gloss Enhancer, Gray
Ink Droplet Size	6.0 pl: Magenta, Yellow, Matte Black, Red, Green, Blue
Ink Type	HP Vivera pigment ink
Ink Cartridges	Blue, Green, Magenta, Red, Yellow, Gray, Photo Black, Matte Black, Light Cyan, Light Gray, Light Magenta, Gloss Enhancer
Ink Cartridge Capacity	4.40 oz (130 ml)

Printers : HP DesignJet Z3200 PostScript 44in Photo Printer

Ink Cartridge Configuration	6 printheads: 1: light magenta & light cyan printhead 2: magenta & yellow printhead 3: photo black & light gray printhead 4: blue & green printhead 5: matte black & chromatic red printhead 6: gloss enhancer & gray printhead
Number of Nozzles	2112 per printhead 1056 per color 12,672 total
Performance	
Print Speed	D/A1 Color Best (Glossy): 12.4 min/page D/A1 Color Normal (Glossy): 7.2 min/page D/A1 Color Draft (Coated): 2 min/page D/A1 Color Normal (Coated): 3.8 min/page
Input Buffer	256 MB
Storage Capacity	80 GB hard drive
Print Archival Life	~ 200 years fade resistance
Waterproofing	Water-resistant on select HP creative and specialty media
Color Accuracy	Median: < 1.6 dE2000 95% Of Colors: < 2.8 dE2000
Color Stability	< 1 dE2000 in less than 5 minutes
Repeatability	Average: < 0.5 dE2000 95% Of Colors: < 1.4 dE2000
Optical Density	2.5 maximum black optical density (4 L* min)
Paper Handling	
Paper Types	Photo: Satin, Gloss, Semi-Gloss, Matte, Baryte Proofing: Semi-Gloss, High-Gloss Contract, Semi-Gloss Contract, Matte Fine Art: Smooth, Textured, Watercolor, Satin, Aquarella, Litho-Realistic, Canvas Self-Adhesive: Indoor, Vinyl, Polypropylene Banner/Sign: Display Film, Indoor Banner, Scrim, Polypropylene, Tyvek, Outdoor, Billboard, PVC-Free Bond/Coated: Bond, Coated, Heavyweight Coated, Super Heavyweight Plus Matte, Colored Technical: Tracing, Translucent Bond, Vellum Film: Clear, Matte, Polyester Backlit Fabric/Textile: Flag, Polyester, Silk
Paper Sizes	Sheets: 8.5 x 11.0 to 44.0 x 66.0" (21.59 x 27.94 to 111.76 x 167.64 cm) Rolls: 11.0 to 44.0" (27.94 to 111.76 cm)
Maximum Paper Width	44.0" (111.76 cm)
Maximum Printable	44.0" x 300' (1.12 x

Printers : HP DesignJet Z3200 PostScript 44in Photo Printer

Area	91.44 m)
Margins	Sheets - Top, Left, Right: 0.2" (5.08 mm) Sheets - Bottom: 0.67 (17.0 mm) Rolls: 0.2" (5.08 mm) all sides <i>Borderless available on glossy/satin roll media</i>
Media Thickness	Up to 31.5 mil (0.8 mm)
Media Weight	Up to 133 lb (500 g/m2)
Maximum Roll Print Length	300.0' (91.44 m)
Maximum Media Roll Diameter	5.3" (13.46 cm)
Document Finishing	Sheet feed, roll feed, automatic cutter
Connectivity	
Computer Interface	Gigabit Ethernet (1000Base-T) Hi-Speed USB 2.0 EIO Jetdirect accessory slot
Network Capable	Wired Ethernet
Printer Language	Adobe PostScript 3, Adobe PDF 1.6, TIFF, JPEG, HP PCL 3 GUI
PostScript Support	Genuine Adobe PostScript 3
OS Compatibility	Microsoft: Vista, Vista x64, XP Home, XP Pro, XP Pro x64, Server 2008 (32/64-bit), Server 2003 (32/64-bit), Windows Terminal Services Apple: Mac OS X v 10.4, 10.5, 10.6 Citrix: MetaFrame
Physical	
Status Display	Front panel display LED light
Front Panel Controls	4 direct access keys (ink levels, loaded paper type, unload paper, form feed & cut) Menu, OK, Up, Down, Back, Cancel, Power
Power Requirements	100 to 240 V AC (±10%), 50/60 Hz (±3 Hz), 2 Amps max
Power Consumption	200 W maximum
Acoustics	Sound Pressure (Active): 49 dB(A) Sound Pressure (Standby): 29 dB(A) Sound Power (Active): 6.5 B(A) Sound Power (Standby): 4.4 B(A)
Certifications	Safety: IEC 60950-1 compliant, EU LVD and EN 60950-1 compliant, certified by

	CSA for Canada and US, Argentina IRAM, Singapore PSB, Russia GOST, China CCIB, Taiwan BSMI	
	Electromagnetic: Compliance for Class B products: EU (EMC Directive), USA (FCC rules), Canada (DoC), Australia (ACA), New Zealand(MoC), China (CCC), Japan (VCCI), Korea (MIC) and Taiwan (BSMI)	
Temperature & Humidity	Operating Temperature: 41 to 104 °F (5 to 40 °C) <i>Recommended: 59 to 95 °F (15 to 35 °C)</i> Storage Temperature: -13 to 131 °F (-25 to 55 °C) Operating Humidity: 20 to 80% Storage Humidity: 0 to 95%	
Dimensions (WxDxH)	69.7 x 27.2 x 41.2" (177.04 x 69.09 x 104.65 cm)	
Weight	189 lb (85.73 kg)	
Packaging Info		
Package Weight		269.0 lb
Box Dimensions (LxWxH)		76.0 x 30.5 x 30.0"