ROLAND SOLJET EJ-640 High-Volume Printer



Rating: 5.0 **Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 11,997.00

Discount:



Ask a question about this product

Manufacturer: Roland

Description

Specifications:

Printing Width *2

Printing technology Piezoelectric inkjet

Media Width 10.2 to 64 in. (259 to 1625 mm)

Thickness Maximum 39 mil (1.0 mm) with

liner

Roll diameter Maximum 8.3 in (210 mm)

Roll weight 88 lbs (40 kg)

Core diameter *1 3 in (76.2 mm) or 2 in (50.8 mm)

Max. 63.6 in. (1615 mm)

Ink cartridges Type Roland DG EJ INK

Capacity 1,000-cc cartridge
Colors CMYKLcLmLk

CMYKKYMC

Print resolution Dots per in Maximum 1,440 dpi

Print Modes	Resolution	Pass	Speed	
		4 COLOR CMYK		
Max Speed (Banner)	360x360	1	1098 ft2/h (102 m2/h)	
Billboard (Banner)	540x360	2	678 ft2/h (63 m2/h)	
High Speed (Banner)	540x360	4	334 ft2/h (31 m2/h)	
Standard (Banner)	720x720	5	258 ft2/h (24 m2/hr)	
High Quality (Banner)	720x1440	9	140 ft2/h (13 m2/h)	
High Speed (Vinyl)	360x720	4	323 ft2/h (30 m2/h)	
Standard (Vinyl)	720x720	6	215 ft2/h (20 m2/hr)	
	720x720	8	161 ft2/h (15 m2/h)	
High Quality (Vinyl)	720x1440	12	108 ft2/h (10m2/h)	
	7 C	OLOR CMYKLcLmLk		
High Speed (Banner)	540x360	8	172 ft/2/h (16 m2/h)	
Standard (Banner)	720x720	10	129 ft2/h (12 m2/h)	
High Quality (Banner)	720x1440	18	65 ft2/h (6 m2/h)	
High Speed (Vinyl)	360x720	8	161 ft2/h (15 m2/h)	
Standard (Vinyl)	720x720	12	108 ft2/h (10m2/h)	
High Quality (Vinyl)	720x1440	20	59 ft2/h (5.5 m2/h)	
Distance accuracy *3 *4	Error of less than $\pm 0.3\%$ of distance traveled, or ± 0.3 mm, whicheve is greater			
Media heating system *5	Print heater	Setting range for the p	Setting range for the preset temperature: 30 to 45°C (86 to 112°F)	
	Dryer	Setting range for the p	Setting range for the preset temperature: 30 to 55°C (86 to 131°F)	
Connectivity		Ethernet (10BASE-T/	Ethernet (10BASE-T/100BASE-TX, automatic switching)	
Power-saving function		Automatic sleep featu	Automatic sleep feature	
Power requirements		AC 100 to 120 V ±109	AC 100 to 120 V ±10%, 11 A, 50/60 Hz or	
		AC 220 to 240 V ±109	%, 5.5 A, 50/60 Hz	
Power consumption	During operation	1450 w	1450 w	
	Sleep mode	75 w		
Acoustic noise level	During operation	•	Temperature: 15 to 32°C (59 to 90°F) [20°C (68°F) or more recommended], Humidity: 35 to 80%RH (no condensing)	
	During standby	Temperature: 5 to 40° condensation)	Temperature: 5 to 40° C (41 to 104° F), humidity: 20 to 80% RH (no condensation)	
Dimensions (with stand)		108in (2,750mm) W x	108in (2,750mm) W x 31in (785mm) D x 59.9in (1,520mm) H	
Weight (with stand)		485 lb (220 kg)		
ncluded items			Dedicated stands, power cord, media clamps, media holders, replacement blade for separating	

Roland VersaWorks System Requirements			
Operating system	Windows® 8, Windows® 7, Windows Vista®, Windows® XP		
CPU	Core™2 Duo, 2.0 GHz or faster recommended		
RAM	2 GB or more recommended		
Video card and monitor	A resolution of 1280 x 1024 resolution or more recommended		
Free hard-disk space	40 GB or more recommended		
Hard-disk file system	NTFS format		

Optical drive DVD-ROM drive

Application software compatible with Cutting and Print&Cut

Adobe® Illustrator® 10, CS, CS2, CS3, CS4, CS5. CS6 CoreIDRAW® 11, 12, X3, X4, X5