Canon imagePROGRAF iPF6450 24in Printer





Rating: 5.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 1,299.00

Discount:

In Stock!
Ready to Order

Ask a question about this product

Manufacturer: Canon

Description

Item: 6554B002AA

UPC: 013803150551

Printing Method	
Printing Technology	12-color 24.0" inkjet printer with non-firing nozzle detection & compensation
Maximum Resolution	2400 x 1200 dpi
Minimum Ink Droplet Size	4.0 pl
Ink Type	Pigment-based
Ink Palette	Cyan, Photo Cyan, Magenta, Photo Magenta, Yellow, Black, Matte Black, Red, Green, Blue, Gray, Photo Gray
Ink Cartridge Configuration	12 cartridges, 6 cartridges per printhead
Number of Nozzles	**Per Color:** 2,560 nozzles **Total:** 30,720 nozzles
Nozzle Pitch	1200 dpi

Printer Language	GARO
Paper Handling	
Paper-Feed Method	Top-loading manual feed, front-loading manual feed
Maximum Printable Area	24.0" x 59.0' (60.96 cm x 18.0 m)
Paper Sizes	**Standard:** Letter, Legal, Ledger, Super B, 10.0 x 12.0", 10.0 x 15.0", 12.0 x 16.0", 13.0 x 22.0", 14.0 x 17.0", 18.0 x 22.0", 16.0 x 20.0", 20.0 x 24.0", 20.0 x 30.0", 300 x 900 mm, A1, A2, A2+, A3, A3+, A4, B2, B3, B4, JIS B2, JIS B3, JIS B4, ANSI D, ANSI C, ARCH A, ARCH B, ARCH C, ARCH D, DIN C2, DIN C3. DIN C4 **Custom - Sheet (Top Load):** 8.0 x 11.0 to 24.0 x 63.0" (20.32 x 27.94 to 60.96 x 160.0 cm) **Custom - Sheet (Front Load):** 8.0 x 16.5 to 24.0 x 36.0" (20.32 x 42.0 to 60.96 x 91.44 cm) **Roll:** 8.0 x 8.0" to 24.0" x 59.0' (20.32 x 20.32 cm to 60.96 cm x 18.0 m)
Borderless Printing Width	A1, A2, A2+, A3+, B2, B4, 10.0" (25.4 cm), 14.0" (35.56 cm), 16.0" (40.64 cm), 17.0" (43.18 cm), 24.0" (60.96 cm)
Maximum Roll Print Length	59.0' (18.0 m)
Paper Types	Plain, coated, photo, proofing, art, sign/CAD
Media Thickness	**Sheet (Top-Load):** 3.2 to 31.4 mil (0.07 to 0.8 mm) **Sheet (Front-Load):** 19.6 to 59.0 mil (0.5 to 1.5 mm) **Roll:** 3.2 to 31.4 mil (0.07 to 0.8 mm)
Cutter	Automatic/Manual
Maximum Media Roll Diameter	5.9" (150 mm)
Core Size	2.0 or 3.0" (5.08 or 7.62 cm)
Connectivity	
Interface	**USB:** Hi-Speed USB 2.0 **Network:** 10/100/1000 Base-T/TX Ethernet
OS Compatibility	**Windows:** Windows 7 (32/64-bit), Vista (32/64-bit), XP (32/64-bit), Server 2003 (32/64-bit), Server 2008 (32/64-bit) **Mac:** OS X 10.5.8 to 10.7x Solaris 9 Red Hat 9
Internal Memory	384 MB
Hard Disk Capacity	250 GB
Physical	
Control Panel	**LCD** **LEDs:** Cut Sheet, Roll Media, Message, Data **Buttons:** Power, Stop, Navigate, OK, Back, Menu, Cut, Feed, Load, 4 directional arrows
Power Requirements	100 to 240 V AC (50 to 60 Hz)
Power Consumption	**Maximum:** 100 W **Standby:** ? 6.0 W **Power Off:** ? 0.5 W
Acoustic Noise	**Sound Pressure (Printing):** ? 47 dB(A) **Sound Pressure (Standby):** ? 35 dB(A) **Sound Power (Printing):** ? 6.4 B(A)
Certifications	International Energy Star Program, Eco Mark (Japan), Law on Promoting Green Purchasing (Japan), GPN, RoHS (Europe/China), Eco Declaration (Europe), WEEE (Europe/India), U.S. Presidential Directives, ErP Directive
Temperature / Humidity	**Operating Temperature:** 59 to 86 °F (15 to 30 °C) **Operating Humidity:** 10 to 80%
Dimensions (WxDxH)	48.3 x 34.3 x 39.4" (122.68 x 87.12 x 100.08 cm)
Weight	154 lb (69.85 kg) including stand
Packaging Info	
Package Weight	154.0 lb
Box Dimensions (LxWxH)	53.0 x 37.0 x 36.5"