

Canon imagePROGRAF iPF830 44in Printer



Rating: 4.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,459.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Canon](#)

Description

Item: 0005C002AA

UPC: 013803248791

Printing Technology	5-Color 44" (111.8 cm) printer
Nozzle Pitch	1200 dpi
Number of Nozzles	Total: 15,360 MBK: 5,120 C, M, Y, BK: 2,560 nozzles each
Print Resolution	2400 x 1200 dpi (Max)
OS Compatibility	Windows® (XP 32-bit/Vista/7/8/8.1) Macintosh® (OSX 10.6.8 - 10.10)
Standard Interface	High-Speed USB 2.0 10/100/1000 Base-T/TX
Minimum Ink Droplet Size	4.0 pl
Ink Tank Capacity	Ink Capacity: 330 ml , 700 ml per color

Printers : Canon imagePROGRAF iPF830 44in Printer

Ink Type	Dye/Pigment Reactive Ink
Hard Drive	320 GB
Media Width	Cut Sheet: 8 to 44" (20.3 to 111.8 cm) Roll Feed: 10 to 44" (25.4 to 111.8 cm)
Media Thickness	2.8 to 31.5 mil (0.07 to 0.8 mm)
Maximum Roll Print Length	Roll Feed: 59' (18 m)
Maximum Media Roll Diameter	5.9" (15.1 cm)
Borderless Printing Width	10, 14, 17, 24, 36, 42" (25.4, 35.6, 43.2, 61, 91.4, 106.7 cm)
Paper-Feed Method	Roll Feed: One roll, front loading, front output Cut Sheet: One sheet, front loading, front output
Languages	GARO (Canon Proprietary), HP-GL/2, HP-RTL
Noise Level	Operation: 52 dB (A) or less Standby: 35 dB (A) or less Acoustic Power: Approx. 6.8 Bels or less
Power	Source: 100 to 240 VAC (50 to 60 Hz)
Power Consumption	Maximum: 190 W or less Standby: 5 W or less Power Off: 0.5 W or less (compliant with Executive Order)
User Replaceable	Print Head: PF-04 Maintenance Cartridge: MC-10, MC-09 Ink Tanks: PFI-307 (330 ml: C, M, Y, BK, MBK) PFI-707 (700 ml: C, M, Y, BK, MBK)
Software	Canon Printer Driver, Printer Driver Extra Kit (Free Layout, Color imageRUNNER Enlargement Copy, Advanced Preview), Direct Print & Share, imagePROGRAF Print Utility4, PosterArtist Lite (PC Only), Print Plug-in for Microsoft Word/Excel/PowerPoint (PC only), Status Monitor, Media Configuration Tool, Optimized Module for AutoCAD
Environmental	Temperature: 59 to 86°F (15 to 30°C) Humidity: 10 to 80%
Dimensions (WxDxH)	75 x 51 x 45" (190.5 x 129.5 x 114.3 cm)
Weight	380 lb (172.4 kg)
Packaging Info	
Box Dimensions (LxWxH)	58.0 x 58.0 x 46.0"