Canon imagePROGRAF iPF9400 60in Printer





Rating: 3.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 4,099.00

Discount:

In Stock!
Ready to Order

Ask a question about this product

Manufacturer: Canon

Description

Item: 6560B002AA

UPC: 013803150681

Printing Method	Inkjet printer with non-firing nozzle detection and compensation
Printing Technology	2400 x 1200 dpi
Maximum Resolution	4.0 pl
Minimum Ink Droplet Size	LUCIA EX Ink (Pigment based)
Ink Type	Cyan, Photo Cyan, Magenta, Photo Magenta, Yellow, Black, Matte Black, Red, Green, Blue, Gray, Photo Gray
Ink Palette	12 individual cartridges
Ink Cartridge Configuration	11.16 or 23.67 fl oz (330 or 700 ml) per color
Ink Cartridge Capacity	PFI-306 MBK Matte Black
Compatible Ink Cartridges	PFI-306 BK Black
	PFI-306 C Cyan

	PFI-306 M Magenta PFI-306 Y Yellow PFI-306 PC Photo Cyan PFI-306 PM Photo Magenta PFI-306 R Red PFI-306 G Green PFI-306 B Blue PFI-306 GY Gray PFI-306 PGY Photo Gray PFI-706 MBK Matte Black PFI-706 BK Black PFI-706 C Cyan PFI-706 M Magenta PFI-706 Y Yellow PFI-706 PC Photo Cyan PFI-706 PM Photo Magenta PFI-706 R Red PFI-706 G Green PFI-706 B Blue PFI-706 GY Gray PFI-706 PGY Photo Gray
Number of Nozzles	2,560 nozzles per color 30,720 nozzles total
Nozzle Pitch	1200 dpi
Paper Handling	
Paper-Feed Method	**Roll Feed:** 1 Roll, front output **Sheet Feed:** 1 sheet, manual feed, front output
Paper Types	Plain, Coated, Photo, Proofing, Art, Sign/CAD
Paper Sizes	US: Letter, Legal, Ledger, Super B, 13.0 x 22.0" (33.02 x 55.88 cm) ISO: A0, A1, A2, A2+, A3, A3+, A4, B0, B1, B2, B3, B4 JIS: B0, B1, B2, B3, B4 ANSI: C, D, E, F ARCH: A, B, C, D, E1, E2, E3 DIN: C0, C1, C2, C3, C4 US Photo 16.0 x 20.0" (40.64 x 50.8 cm) Poster: 20.0 x 30.0" (50.8 x 76.2 cm), 30.0 x 40.0" (76.2 x 40.64 cm), 42.0 x 60.0" (106.68 x 152.4 cm), 44.0 x 62.0" (111.76 x 157.48 cm), 50.0 x 70.0" (127.0 x 177.8 cm), 54.0 x 76.0" (137.16 x 193.04 cm), 60.0 x 84.0" (152.4 x 213.36 cm) Other: 8.0 x 10.0" (20.32 x 25.4 cm), 10.0 x 15.0" (25.4 x 38.1 cm), 10.0 x 12.0" (25.4 x 30.48 cm), 12.0 x 16.0" (30.48 x 40.64 cm), 14.0 x 17.0" (35.56 x 43.18 cm), 18.0 x 22.0" (45.72 x 55.88 cm), 20.0 x 24.0" (50.8 x 60.96 cm) **Custom:** 8.0 x 8.0 to 60.0 x 63.0" (20.32 x 20.32 to 152.4 x 160.0 cm) **Roll Width:** 10.0 to 60.0" (25.4 to 152.4 cm) **Roll Print Length:** Up to 59.1' (18.0 m)
Borderless Printing Width	10.0" (25.4 cm), 14.0" (35.56 cm), 17.0" (43.18 cm), 24.0" (60.96 cm), 36.0" (91.44 cm), 42.0" (106.68 cm), 44.0" (111.76 cm), 50.0" (127.0 cm), 60.0" (152.4 cm) JIS B2 (20.28" / 51.5 cm), JIS B0 (40.55" / 103.0 cm), ISO A1 (23.39" / 59.4 cm), ISO A0 (33.11" / 84.1 cm)
Media Weight	70 to 470 g/m2
Media Thickness	2.8 to 31.0 mil (0.07 to 0.8 mm)
Maximum Media Roll Diameter	6.0" (15.24 cm)
Core Size	2.0, 3.0" (5.08, 7.62 cm)
Connectivity	
Interfaces	High-Speed USB 2.0 10 / 100 / 1000 Base-T / TX Ethernet
Network Protocols	IPX / SPX, SNMP (Canon-MIB compatible), HTTP, TCP / IP, AppleTalk
OS Compatibility	**Windows:** XP, Vista (32 / 64-bit) Windows 7 (32 / 64-bit) Macintosh OS X
Input Buffer	640 MB
Hard Drive Capacity	250 GB
Printer Language	GARO
Physical	
Control Panel	**LCD** **LEDs** Message, Roll Media, Cut Sheet Media **Buttons:** Power, Menu, OK, Stop, Navigate, Back, Cut, Feed, Load, 4 directional arrows

Power Requirements	100 to 240 VAC (50 to 60 Hz)
Power Consumption	**Maximum:** 190.0 W **Standby:** ? 6.0 W **Power Off:** ? 0.5 W
Acoustic Noise	**Operation:** ? 68 dB(A) **Standby:** ? 35 dB(A)
Certifications	International Energy Star Program (worldwide), Law on Promoting Green Purchasing (Japan), GPN, RoHS directive, IT Eco Declaration (Europe), WEEE, U.S. presidential directives, J-MOSS (Green Mark), Chinese RoHS, ErP Lot6 (Europe)
Temperature / Humidity	**Operating Temperature:** 59 to 86°F (15 to 30°C) **Operating Humidity:** 10 to 80%
Dimensions (WxDxH)	90.5 x 30.2 x 45.0" (229.87 x 76.71 x 114.3 cm)
Weight	362.0 lb (164.2 kg) including stand
Packaging Info	
Package Weight	562.0 lb
Box Dimensions (LxWxH)	98.0 x 48.5 x 40.0"