

Canon XF200 HD Camcorder (PAL)



Rating: 5.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,249.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Canon](#)

Description

Product Highlights

Camcorder : Canon XF200 HD Camcorder (PAL)

- 1920 x 1080, 1/2.84" CMOS Sensor
- 20x Lens with Zoom, Focus, Iris Rings
- 50 Mbps MPEG-2 & 35 Mbps MP4 Recording
- 4:2:2 Color Sampling
- 50i/p and, 25p Frame Rates
- Dual CF and Single SDXC Card Slots
- Dual XLR Inputs, Four Channels of Audio
- Orientable Hand Grip
- HDMI, WiFi, and Ethernet

Image Sensor Size

Video System

Color Filter System

Total Pixels

Effective Pixels

Zoom Range

Focal Length

35mm Equivalent Focal Length

Aperture Range

Minimum Focus Distance

Zoom Speed

Filter Diameter

Shutter Speed

Image Stabilization

White Balance

Supported Video Formats / Codecs

Resolutions and Frame Rates

1/2.84" CMOS Sensor

PAL

RGB Primary color filter

3.09 MP (2208 x 1398)

2.91 MP (2136 x 1362)

20x Optical

1.5x, 3x, 6x Digital

3.67 to 73.4mm

28.8 to 576mm (with Dynamic IS)

f/1.8 to f/16

23.6" (60 cm) Across zoom range

10 mm (1 cm) Wide Macro setting

Variable speed / Constant speed (16 levels); Fast, Normal, or Slow

58 mm

1/18 to 1/2000 depending on frame rate

Dynamic IS and Powered IS

Five-axis image stabilization

-50 to +50 White balance offset for RGB

AVCHD, MPEG4

MXF (CF card):

50 Mbps: 1920 x 1080 / 50i, 25p; 1280 x 720 / 50p, 25p

35 Mbps: 1920 x 1080 / 50i, 25p; 1440 x 1080 / 50i; 1280 x 720 / 50p, 25p

25 Mbps: 1440 x 1080 / 50i, 25p

MP4 (SD card):

35/24 Mbps: 1920 x 1080 / 50p, 25p

17 Mbps: 1280 x 720 / 50p

9 Mbps: 1280 x 720 / 25p

3 Mbps: 640 x 360 / 25p

MXF only:

128 GB CF Card: Up to 320 mins (1080/50i @ 50 Mbps)

128 GB SD Card: Up to 8 hours (MP4/50p @ 35 Mbps)

0.45" Color EVF

Pixel Count: Approximately 1.5MP

3.5" (8.77 cm) OLED

2 x Compact Flash

1 x SDXC

USB 2.0 Mini-B, output only

1 x HDMI

2 x XLR female

1 x 3.5 mm Stereo mini jack

2/4-Channel, Linear PCM, 16-Bit, 48 kHz (MXF)

3.5 mm Mini 4-pole Audio/Video Out

3.5 mm Stereo mini jack

2.5 mm Mini jack

Cold shoe

Operation: Approx. 23 to 113°F / -5 to 45°C, 60% RH

Performance: Approx. 32 to 104°F / 0 to 40°C, 85% RH

6.3 x 7.9 x 13.9" / 16.0 x 20.1 x 35.3 cm

(including lens hood with barrier, eyecup, and microphone holder)

4.2 lb / 1.9 g

Slow and Fast Motion Recording

Maximum Recording Time

Viewfinder

Touchscreen

Media Card Slots

USB Terminal

HDMI Output

Audio In

A/V Output

Headphone Out

Remote Control Input

Accessory Shoe

Operating Temperature

Dimensions

Weight