

HUBSAN X4 Pro Low Edition Quadcopter with 1080p Camera and 1-Axis Gimbals



Rating: 3.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 274.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hubsan](#)

Description

Product Highlights

- Capture 1080p Video with HBS1080P
- 1-Axis Gimbal for GoPro HERO / HBS1080P
- 1-Axis Gimbal for Smartphone
- GPS-Based Flight Control System
- FPV Transmitter with Built-In Screen
- Automatic Return to Home (RTH)
- Flight Battery and Charger Included
- Built-In Parachute w/ Redundant Battery

Performance

Flying Time	Without Payload: 30 minutes With 1-Axis Gimbal: 27 minutes With 3-Axis Gimbal: 23 minutes
Maximum Angular Velocity	Heading Axis: 150°/second
Maximum Tilt Angle	35°
Maximum Ascent/Descent Speed	13.1' feet per second 4 m/second
Maximum Speed	13.1' to 19.7' feet per second 4 to 6 m/second
Maximum Flight Altitude	32.8 to 820.2' / 10 to 250 m (adjustable)
Maximum Wind Speed Resistance	Level 4
Flight Control System	GPS
Sensors	Compass
Flight Battery	
Capacity	7000 mAh
Chemistry	Lithium-polymer (LiPo)
Voltage	11.1 VDC
Maximum Charging Power	50 W
Charging Temperature	32 to 104°F / 0 to 40°C
Operating Temperature	14 to 104°F / -10 to 40°C
Storage Temperature	Less than 3 Months: -4 to 113°F / -20 to 45°C More than 3 Months: 72 to 82°F / 22 to 28°C
Weight	13.6 oz / 384 g
Charger	
Voltage	12 VDC
Output Power	60 W
Handheld Transmitter	
Frequency	Control: 2.4 GHz Video Receiver: 5.8 GHz (analog)
Range	Up to 3280.8' / 1000 m line-of-sight
Display	Built-in color display for FPV monitoring
Control Mode	Mode 2 (left stick throttle)
Power Requirements	AA batteries
Camera	
Model	HBS1080P
Sensor	Mode: AR0330 Size: 1/3" Resolution: 3 MP
Lens	FOV: Up to 170° (depending on camera settings) Elements: 6
Video Recording	1920 x 1080p at 30 fps
Still Capture	12.2 MP (4032 x 3024) -- via interpolation
File Formats	Video Codec: H.264 Wrapper: MOV
Recording Media	MicroSD: Class 4 or 6; 4 to 32GB
Connectivity	Note: Card must be formatted Fat32 1 x Micro-USB for charging and data I/O
Power Consumption	Operation: 1.9 W Standby: 1.33 W
Power Requirements	3.7 V 650 mAh LiPo battery
Operating Temperature	14 to 104°F / -10 to 40°C
Storage Humidity	30 to 90%
Parachute	
Power Requirements	380 mAh 3.7 V LiPo battery
Operating Temperature	14 to 140°F / -10 to 60°C
Charging Temperature	32 to 104°F / 0 to 40°C
Storage Temperature	Less than 3 Months: -4 to 113°F / -20 to 45°C More than 3 Months: 72 to 82°F / 22 to 28°C
Dimensions	3.1 x 3.1 x 4.1" / 79 x 78 x 105 mm
General	
Operating Temperature	14 to 104°F / -10 to 40°C
Dimensions	11.8 x 11.8 x 8.1" / 300 x 300 x 205 mm
Weight	3 lb / 1.4 kg
Packaging Info	
Package Weight	14.6 lb
Box Dimensions (LxWxH)	23.3 x 19.9 x 11.8"

