Sony PXW-X180 Full HD XDCAM Handheld Camcorder













Rating: 3.0 **Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,249.00

Discount:



Ask a question about this product

Manufacturer: Sony

Description

Product Highlights

- Three 1/3" Exmor CMOS Sensors
- XAVC Intra and Long GOP Codecs
- MPEG HD 422, AVCHD, & DV Codecs
- G Lens with 25x Optical Zoom
- Electronic Variable ND Filter
- Dual SxS Memory Card Slots
- 3G/HD-SDI & HDMI Output
- MP4 Proxy Recording to SD Card
- 0.5" OLED Viewfinder
- Wi-Fi Remote Control via Included Module

Camera Imaging Device Effective Pixels (H x V) Sensitivity

S/N Ratio Shutter Speed White Balance GPS Wi-Fi NFC

Built-In ND Filters

Lens
Type
Zoom Ratio
Focal Length
35mm Equivalent Focal Length

Aperture Focus

Minimum Focus Distance
Image Stabilizer
Filter Diameter

Recording Video Recording Format 3 x 1/3" type Exmor CMOS sensor 1920 x 1080 F9 (typical) (1920 x 1080/59.94i mode) F10 (typical) (1920 x 1080/50i mode) 60 dB (Y) (typical) 1/32 to 1/2000 sec Present (3200K), A, B Yes

Yes Clear, 1/4 to 1/128 variable

Fixed
25x (optical), servo/manual
3.7 to 92.5 mm
26 to 650 mm
f/1.6 to f/11, and closed
Autofocus / manual focus selectable
Wide: 0.39" (10 mm)
Tele: 31.5" (800 mm)
ON/OFF/ACTIVE selectable, shift lens
82 mm

XAVC-Intra

1920x1080 59.94i: 111 Mbps max 1920x1080 50i: 112 Mbps max 1920x1080 29.97p: 111 Mbps max 1920x1080 25p: 112 Mbps max 1920x1080 23.98p: 89 Mbps max 1280x720 59.94p: 111 Mbps max 1280x720 50p: 112 Mbps max

XAVC-Long

1920x1080 59.94i, 50i: 50/35/25 Mbps max 1920x1080 59.94p, 50p, 29.97p, 25p, 23.98p: 50/35 Mbps max 1280x720 59.94p, 50p: 50 Mbps max

MPEG HD422

 $1920x1080\ 59.94i,\ 50i,\ 29.97p,\ 25p,\ 23.98p:\ 50\ Mbps\ max\\ 1280x720\ 59.94p,\ 50p,\ 29.97p,\ 25p,\ 23.98p:\ 50\ Mbps\ max$

MPEG HD420

1920x1080 59.94i, 50i, 29.97p, 25p, 23.98p: 35Mbps max 1440x1080 59.94i, 50i: 35 Mbps max 1280x720 59.94p, 50p: 35Mbps max

AVCHD

1920x1080 59.94p, 50p: 28 Mbps max 1920x1080 59.94i, 50i, 29.97p, 25p, 23.98p: 24 Mbps max 1280x720 59.94p, 50p: 24 Mbps max

DVCAM

720x480 59.94i: 25 Mbps 720x576 50i: 25 Mbps Slow & Quick Motion Function

Audio Recording Format

Interface Input Audio Output HDMI Output SDI Output

Composite Output / GENLOCK-IN

USB

Timecode Input & Output

Remote
DC Input
Shoe Mounts
Headphone Output
Built-In Microphone
Monitoring
Viewfinder

LCD

Recording Media

Slots

General

Power Requirements

Power Consumption

Battery Operating Time

Operating Temperature Storage Temperature Dimensions (WxHxD) Weight

Packaging Info Package Weight

Box Dimensions (LxWxH)

Proxy

1280x720: 9 Mbps 640x360: 3 Mbps 480x270: 1 Mbps 480x270: 500 Kbps

1920x1080p: Frame rate selectable 1 to 60p (depends on Recording

Format)

1280x720: 1 to 120p (depends on Recording Format)

Angle of view becomes smaller over 60fps

LPCM, AC-3 (AVCHD): 2 channel

LPCM (XAVC/MPEG2/AVCHD/DVCAM), Dolby Digital (AVCHD): 2

channel

2 x XLR 3-pin, female

1 x 3.5 mm

1 x HDMI, Type A

1 x 3G-SDI, BNC connector

1 x BNC connector

1 x USB 2.0, mini-B

1 x type A (for Wireless LAN module)

1 x BNC connector

1 x 2.5 mm

1 x DC jack

1 x Multi Interface shoe

1 x 3.5 mm

Omni-directional stereo electret condenser microphone

0.5" (1.27 cm) color OLED

2.36 million dots

3.5" (8.89 cm) color LCD monitor

Aspect ratio: 16:9 1.56 million dots

2 x ExpressCard/34; supports SxS PRO+ and SxS-1 memory cards (for

XAVC/MPEG2/AVCHD/DV)
1 x SD/SDHC/SDXC (for Proxy)
1 x SD/SDHC/SDXC (for Utility)

19.5 VDC (AC Adaptor)

14.4 VDC (battery pack)

Approx. 19.9 W (while recording with LCD Off, EVF On when the

external device connector is not used)

With battery pack BP-U90: approx. 4 hours (While recording with LCD

Off, EVF On when the external device connector is not used)

With battery pack BP-U60: approx. 2 hours, 35 minutes (While recording with LCD Off, EVF On when the external device connector is not used)

With battery pack BP-U30: approx. 1 hours, 15 minutes (While recording with LCD Off, EVF On when the external device connector is not used)

32 to 104°F (0 to 40°C)

-4 to 140°F (-20 to 60°C)

 $7.54 \times 7.93 \times 16.22$ " (19.15 x 00.15 x 41.20 cm); without protrusions

Approx. 5.95 lb (2.7 kg); body only

Approx. 7.05 lb (3.2 kg); with lens hood, eyecup, battery pack BP-U30,

SxS memory card

12.55 lb

17.0 x 10.9 x 10.7"